Application No. : 10/814,156

Art Unit: 3725

IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

2

3

5

6

7

8

9

11

12

13

Claims 1-20 (Canceled)

1 Claim 21. (New) A saw blade for a reciprocating power saw, comprising:

a flat, elongated mounting arm having a saw mounting end adapted for attachment to the

reciprocating saw and having a second end;

4 a flat, elongated connector arm having a first end integrally attached to the second end of the

mounting arm, the connector arm and the mounting arm forming a dihedral angle of about 90°;

a flat, elongated cutting blade having a first end integrally connected to the second end of the

connector arm and having a second end, the cutting blade having at least one cutting edge defined by

a plurality of teeth, the cutting blade and the connector arm forming a dihedral angle of about 90°, the

cutting blade and the mounting arm being parallel to each other and extending in opposite directions

10 from the connector arm; and

at least one stabilizer attached to said mounting arm and said connector arm;

wherein said mounting arm, said connector arm and said cutting blade is of unitary construction,

and wherein said cutting blade is offset from said mounting arm by a distance substantially equal to the

length of the connector arm;

2

Attorney Docket No. 22349.00 Confirmation No. 7368

Application No. : 10/814,156

Art Unit: 3725

- whereby the cutting blade is capable of being placed flush against one surface of a 90° corner in order to cut around the corner.
- 1 Claim 22. (New) The saw blade according to claim 21, wherein said at least one stabilizer includes
- 2 two stabilizers.
- 1 Claim 23. (New) The saw blade according to claim 22, wherein said stabilizers are gusset plates.
- 1 Claim 24. (New) The saw balde according to claim 23, wherein said gusset plates are disposed in a
- 2 transversely centrally aligned position on opposite sides of said connector plate
- 1 Claim 25. (New) The saw blade according to claim 21, further comprising a reinforcing rib attached
 - 2 to a top surface of said mounting arm.